

A red line graphic that starts with a sharp peak, followed by several smaller peaks and valleys, resembling a signal or waveform, extending across the page.

# PTFE HEAT SHRINK TUBING (SHRINK RATIO 4:1)

Optinova PTFE heat shrink tubing has the outstanding properties of PTFE offering excellent chemical resistance, high temperature resistance, excellent electrical insulation and low friction.

Shrink temperature is approximately 340°C.

Heat shrink tubing is the optimum method to offer a protective jacket for applications in extreme environments of heat, corrosion, shock and moisture.

Dimensions below are examples only.

We can produce most sizes according to customer needs.

<b>PTFE Heat Shrink Tubing 4:1</b>			
Order-nr	Expanded ID mm	Rec. ID mm	Wall mm
	mm		nom.
5/64"	1.98	0.64	0.22
1/8"	3.18	0.94	0.25
3/16"	4.75	1.27	0.30
1/4"	6.35	1.60	0.30
5/16"	7.92	2.00	0.30
3/8"	9.52	2.44	0.30
7/16"	11.13	2.85	0.30
1/2"	12.70	3.66	0.38
9/16"	14.27	3.94	0.38
5/8"	15.88	4.52	0.38
1 1/16"	17.45	5.03	0.38
3/4"	19.05	5.70	0.38
7/8"	22.23	6.20	0.38
1"	25.40	7.06	0.38

Delivery in length of 1,22 meters or on spools/coils upon request colored heatshrinkable tubing possible on request, minimum quantity 150 meters.

