



YDPU2.E151086 Tubing, Extruded Insulating - Component

[Page Bottom](#)

Tubing, Extruded Insulating - Component

[See General Information for Tubing, Extruded Insulating - Component](#)

THAI SCANTUBE CO LTD

E151086

143 MOO 1 NONGSAMED-BOTHONG RD
BO-KWANGTHONG BOTHANG
CHON BURI, 20270 THAILAND

Cat. No.	Max V	Max Oper Temp	Shrinkdown Class	Col Recognized	Max Temp Rated Oil Resistance * °C	VW-1 Rated #
Nonheat shrinkable PTFE tubing.						
Scantube PTFE-1	150	200	—	Natural	—	Yes
Scantube PTFE-2	300	200	—	Natural	—	Yes
Scantube PTFE-3	600	200	—	Natural	—	Yes

Tubing is considered to comply with the optional VW-1 flammability requirements only if it is so marked.

Marking: Company name, the catalog number or equivalent, and temperature rating in degrees C appear on tags attached to both ends of the tubing or on the shipping spool label or smallest unit container.

[Last Updated](#) on 1994-06-25

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".